


## SHEET1

| Rev: | Date:    | Ву  | Chk | Description |
|------|----------|-----|-----|-------------|
| A.1  | 9/18/12  | PJE | RAW | EC0 0045    |
| A.2  | 10/06/12 | JWW | PJE | EC0 0192    |







技术参数:

最高转速: 200RPM 最高温度: 125°C 最大压力: 10BAR 介质: 气 真空

| Drawn   | JSM | 6/2/03   |
|---------|-----|----------|
| Checked | PJE | 13/43/05 |
| Checked | PJE | 11/36/08 |

CUSTOMER APPROVAL/DATE:

THIS DOCUMENT CONTAINS INFORMATION SHICH IS PROPRIETARY

TO DYNAMIC SEALING TECHNOLOGIES.INS (HIDENY) NO REPRODUCTION

OR PUBLICATION OF THIS DOCUMENT OR IT IS CONTENTS, IN SHOLE OR

PART SHALL BE MADE WITHOUT THE WRITTEN CONSENT FROM HIDNEY

TOLERANCE **EXCEPT AS NOTED** X.X ±.125 ± 0.15 X.XX  $x.xxx \pm 0.005$ ANGLES ± 0.5°

SHAFT MEL/PLTING: **CARBON STL** 

94-62 RC OXIDE BLK

SHAFT MEL/PLTING:

CARBON STL BLK OXIDE

深圳市欣德利机电设备有限公司

TEL:0755-27222664

CUSTOMER:

STOCK

P/N:

REV: A 4

THIRD ANGLE PROJECTION: