## Generated by Foxit PDF Creator © Foxit Software http://www.foxitsoftware.com For evaluation only.

## Chk Rev: Date: By Description 9/18/12 PJE EC0 0045 A.1 RAW 10/06/12 JWW PJE A.2 EC0 0192

	186	
45°	10 41	
4-M6 PCD84 4-Ø25 PCD41 深1.4	020	Ø94
4-PT3/8-	4-PT3/8	


CUSTOMER APPROVAL/DATE:

THIS DOCUMENT CONTAINS INFORMATION SHICH IS PROPRIETARY

TO DYNAMIC SEALING TECHNOLOGIES. INS (HIDENY) NO REPRODUCTION

OR PUBLICATION OF THIS DOCUMENT OR IT IS CONTENTS, IN SHOLE OF

PART SHALL BE MADE WITHOUT THE WRITTEN CONSENT FROM HIDNEY



技术参数: 最高转速: 200 RPM 最高温度: 185°C

SHEET1

最大压力: 350BAR

介质: 液压油 水

THIRD AND E DOO LECTION

THIRD ANGLE PROJECTION:		

Drawn	JSM	6/2/03
Checked	PJE	13/43/05
Checked	PJE	11/36/08

x.xxx ± 0.005 ANGLES ± 0.5°

X.X

X.XX

SHAFT MEL/PLTING: CARBON STL 94-62 RC BLK OXIDE

SHAFT MEL/PLTING:

CARBON STL BLK OXIDE

TOLERANCE

**EXCEPT AS NOTED** 

±.125

± 0.15

深圳市欣德利机电设备有限公司

TEL:0755-27222664

CUSTOMER:

STOCK

P/N: REV: A 4