


Technical drawing of the PT1/4-PT3/8 adapter showing dimensions and connection types.

- Dimensions:**
 - Total length: 129
 - Distance from mounting flange to centerline: 31
 - Mounting flange thickness: 11
 - Flange diameter: Ø18
 - Threaded section diameter: Ø9
- Connections:**
 - Left side: M16X1.5 LH (Left Hand Thread)
 - Bottom: PT1/4 (Parallel Thread)
 - Right side: NPT3/8 (National Pipe Thread)

技术参数：
最高转速：12000RPM
最高温度：125℃
最大压力：50BAR
介质：冷却液

THIRD ANGLE PROJECTION:



Drawn	JSM	6/2/03
Checked	PJE	13/43/05
Checked	PJE	11/36/08

CUSTOMER APPROVAL/DATE:

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY TO DYNAMIC SEALING TECHNOLOGIES, INC. (HIDENY) NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR ITS CONTENTS, IN WHOLE OR PART SHALL BE MADE WITHOUT THE WRITTEN CONSENT FROM HIDENY

TOLERANCE
EXCEPT AS NOTED

X.X	±.125
X.XX	± 0.15
X.XXX	± 0.005
ANGLES	± 0.5°

SHAFT MEL/PLTING:

CARBON STL
94-62 RC
BLK OXIDE

SHAFT MEL/PLTING:

CARBON STL
BLK OXIDE

HIDNEY

深圳市欣德利机电设备有限公司

TEL:0755-27222664

CUSTOMER:

STOCK

P/N:

REV:

A 4