


Generated by Foxit PDF Creator © Foxit Software
http://www.foxitsoftware.com For evaluation only.

SHEET1

Rev:	Date:	By	Chk	Description
A.1	9/18/12	PJE	RAW	ECO 0045
A.2	10/06/12	JWW	PJE	ECO 0192



技术参数：
最高转速：150RPM（可定制800RPM）
最高温度：125℃
最大压力：10BAR
介质：气 真空

Drawn	JSM	6/2/03
Checked	PJE	13/43/05
Checked	PJE	11/36/08

TOLERANCE EXCEPT AS NOTED	
x.x	±.125
x.xx	± 0.15
x.xxx	± 0.005
ANGLES ± 0.5°	

SHAFT MEL/PLTING:	
CARBON STL	RC
BLK	OXIDE

SHAFT MEL/PLTING:	
CARBON STL	RC
BLK	OXIDE

CUSTOMER APPROVAL/DATE:

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY TO DYNAMIC SEALING TECHNOLOGIES, INC. (HIDNEY). NO REPRODUCTION OR PUBLICATION OF THIS DOCUMENT OR ITS CONTENTS, IN WHOLE OR PART, SHALL BE MADE WITHOUT THE WRITTEN CONSENT FROM HIDNEY.

HIDNEY
深圳市欣德利机电设备有限公司
TEL:0755-27222664

CUSTOMER: STOCK

P/N: REV: A 4

THIRD ANGLE PROJECTION:

