




SHEET1

Rev:	Date:	By	Chk	Description
A.1	9/18/12	PJE	RAW	EC0 0045
A.2	10/06/12	JWW	PJE	EC0 0192



技术参数：

最高转速：150RPM（可定制800RPM）

最高温度：125℃

最大压力：10BAR

介质：气 真空

Drawn	JSM	6/2/03
Checked	PJE	13/43/05
Checked	PJE	11/36/08

TOLERANCE
EXCEPT AS NOTED

x.x ±.125

x.xx ± 0.15

x.xxx ± 0.005

ANGLES ± 0.5°

SHAFT MEL/PLTING:

CARBON STL

94-62 RC

BLK OXIDE

SHAFT MEL/PLTING:

CARBON STL

BLK OXIDE

CUSTOMER APPROVAL/DATE:

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY
TO DYNAMIC SEALING TECHNOLOGIES.INS (HIDENY) NO REPRODUCTION
OR PUBLICATION OF THIS DOCUMENT OR IT IS CONTENTS,IN SHOLE OR
PART SHALL BE MADE WITHOUT THE WRITTEN CONSENT FROM HIDNEY**HIDNEY**

深圳市欣德利机电设备有限公司

TEL:0755-27222664

CUSTOMER:

STOCK

P/N:

REV:

A 4

THIRD ANGLE PROJECTION:

